

# Innovative Solutions for Process Analytics

Biotech and Biopharma Upstream and Downstream



# Continuous Innovation for Biotech and Biopharma

More measurement parameters and less measurement error yield tighter process control

“With our pioneering sensor technology, we solve biopharma challenges.”

## Complete Portfolio

Measure all critical process parameters which enable the holistic understanding and control of your process.

## Seamless Integration


Minimize the time and effort required to discover, procure, validate, and effectively utilize a Hamilton sensor.

## Highest Quality

Benefit from products with the highest manufacturing standards to meet or exceed all FDA and GMP regulatory requirements.

## Process Analytics Know-how

Hamilton provides 30+ years of experience of process sensors developed for biopharma applications.




# The Intelligent Sensor Revolution

Over 95% of process engineers surveyed find value in using intelligent sensors


Less than half of engineers felt they fully utilized their smart sensor. The key to getting the most out of your smart sensor is choosing the implementation that best fits your application. Hamilton offers two versions of smart sensors each equipped with our best-in-class measurement technology.

## Benefits of Replacing Analog with Intelligent Sensors



Example based on Hamilton pH Arc Sensors

### Cost Comparison



#### ► Analog Sensors

Traditional analog sensors offer the lowest sensor cost which is ideal for implementations that discard the sensor after each run. They rely on a transmitter to read the sensor's electrochemical signal (ECS) and transmit it to the process control system.


#### ► Digital Sensors

##### Memosens

Digital sensors eliminate signal errors from electromechanical noise near the cable and reduce maintenance cost by enabling in-lab calibration instead of at-line. This is accomplished with an integrated processor to convert the electrochemical signal to a digital output.

#### ► Arc Intelligent Sensors

Intelligent sensors have the lowest start-up and operating costs. They provide advanced alarms, troubleshooting, quality indicators, and diagnostics simultaneously to the control system and to an optional mobile device. An integrated micro-transmitter eliminates a point of failure by directly connecting the sensor to the PCS.



# A Trusted Partner



## The top bioreactor manufacturers deliver reactors with Hamilton sensors installed

Bioreactor and fermenter performance is dependent on having reliable access to actionable data. Manufacturers choose Hamilton's diverse product offering to deliver to their customers relevant process parameters with exceptional life and low maintenance.

### Retrofitting Existing Reactors

Hamilton offers sensors that are compatible with any bioreactor and provide exceptional measurement stability and sensor life. Upgrading to an intelligent sensor will lower operating costs with automatic reporting, batched in-lab calibration, quality indicators, and wireless troubleshooting.

### Next Generation Systems

In recent years bioreactor manufacturers have incorporated 4–20 mA inputs to enable direct input from intelligent sensors. Now they are taking the next step by incorporating digital control of the sensors. This enables the user to check the sensor health, calibrate, and troubleshoot all from the reactor controller.

# New Tools

## Dissolved CO<sub>2</sub> CO<sub>2</sub>NTROL

The first solid-state sensor designed to directly measure DCO<sub>2</sub> in bioprocesses. The sensor provides a low maintenance, in-line measurement for the control of DCO<sub>2</sub>. This parameter is useful for optimizing cell viability, product yield, and when scaling a process up or down.

## Cell Density Sensors Incyte Arc (VCD) and Dencytee Arc (TCD)

Real-time measurement of Viable Cell Density and Total Cell Density provides continuous data resulting in faster optimization of feeding and harvesting strategies.


## Single-Use pH, DO, VCD, and COND

Hamilton developed a gamma sterilizable glass pH sensor that arrives factory calibrated and can be stored dry for up to 18 months. This can be delivered in the bag ready to use alongside Hamilton's single-use DO, VCD, and Conductivity solutions.


1x

## ArcAir Monitoring and Configuration Tools

Transform any Bluetooth-enabled iOS, Android, or PC device into a potent troubleshooting tool at no cost with ArcAir. Establishing a seamless Bluetooth connection, ArcAir grants comprehensive access to all your sensor data. For a more enriching experience, consider upgrading to our advanced version to unlock the full potential of our GMP package.



# Seamless Scale-up to Production



Sensors that last longer and require less maintenance

Hamilton is known for high quality materials and craftsmanship that result in exceptional sensor life.

With the introduction of the Arc sensors Hamilton took ownership of the measurement loop and pioneered advances in sensor calibration, troubleshooting, connectivity, and documentation.



## Start Up

Hamilton assists you to better understand the functionality and use of your sensors with a familiarization demonstration. Trained service engineers are available to commission, qualify, and verify your sensor installation and deliver audit-quality reports that can be shared with your regulatory body.



## Calibration

On-site calibrations require a lot of preparation and logistic effort. Arc sensors can be calibrated in the lab and stored ready to use on the shelf.



## Cleaning

Cleaning in Place (CIP) and Sterilization in Place (SIP) are very challenging treatments for the functionality of sensors. Hamilton sensors are engineered to achieve no offset and no drift shortly after cleaning.



## Maintenance and Troubleshooting

Wirelessly troubleshoot up to 30 sensors at a time without having to enter the production environment. The sensor's quality indicator as well as errors and warnings are easily accessible via the ArcAir App on the Arc View Mobile.



## Plant Expansion

Arc sensors eliminate the need for costly transmitters and simplify wiring with a variety of analog and digital communication options.



## Documentation

Best practices require documentation of sensor calibration, communication verification, and post-process sensor verification. This is normally a manual process, but with Arc reports are generated automatically. The reports are saved in an encrypted GMP-compliant database, printed, and signed for compliance to 21 CFR Part 11 and Eudralex Vol. 4 Annex 11.

# Product Offering

## Single-Use Sensors

Reusable sensors are commonly used in single-use applications but require additional handling, sterilization, and insertion devices. Hamilton adapted these proven sensor technologies into single-use options that come from your single-use supplier: pre-installed, precalibrated, and gamma sterilized.



### Reusable Electronic

(not in media contact)



pH



oDO



VCD



Cond

### Single-Use Sensor Element

(wetted part)



### Compatible with Existing Single-Use Reactor

Hamilton's single-use solutions fit in a variety of different reactor styles and have already been evaluated for performance by many of the top single-use system providers.

	pH	Dissolved Oxygen	Viable Cell Density	Conductivity
Rigid-Wall	✓	✓	✓	✓
Stirred-Tank	✓	✓	✓	✓




### Factory Calibration Labels

Every single-use sensor comes with factory calibration data printed on the sensor tag. This data can be scanned into ArcAir with the 2D barcode, manually input, or directly entered into the bioreactor control system.

# Single-Use Sensors Biopharmaceutical CPPs and KPIs


## SINGLE-USE FACILITY



# Product Offering

## Reusable Sensors

For more than 25 years, Hamilton has manufactured reusable sensors to meet the evolving needs of pharmaceutical and biotechnology upstream (USP) and downstream (DSP) customers. Our extensive product selection is certified to meet or exceed all FDA and GMP regulatory standards.



### Measurement Parameters

All relevant measurement parameters for BioPharma applications are part of the Hamilton portfolio.




### Electrical Connectors

Regardless of which electrical connector, analog or digital, Hamilton provides sensors with the compatible head.



# Reusable Sensors Biopharmaceutical CPPs and KPIs

Every step of the biopharmaceutical process has specific requirements for sensors to monitor and control it precisely. The roadmap below shows the individual recommendations from the Hamilton portfolio.



# Sensor Families

## EasyFerm Bio

The EasyFerm Bio families of pH and ORP sensors are ideal for biotech applications, like fermentations, where autoclavations, steam sterilizations (SIP), and cleaning in place (CIP) procedures occur frequently. Available with the innovative Arc technology.

### BENEFITS

- Stable measurement signals after steam sterilization, autoclaving, and CIP
- Drift-free measurement
- Ceramic diaphragm
- Wetted parts according to USP class VI
- Available as ORP sensor
- EasyFerm Bio is bio-compatible (USP 31, 2008, chapter 87)



\*Memosens

## Polilyte Plus

The Polilyte Plus pH families are ideal for low conductivity and long term stability. The sensor portfolio covers a wide range of applications: in biopharma they are ideal for CIP preparation skids and monitoring of the disinfection. All members will have the same reference electrolyte Polisolve Plus and use the Single Pore technology but will have different pH glasses.

### BENEFITS

- Greater variety of applications due to different pH glasses
- No clogging due to single pore technology
- Highly reproducible measurements
- Very stable over long periods of time
- Upside-down mounting possible with VP connector head
- Available as ORP sensor



## VisiFerm Family

The VisiFerm is the first optical process sensor for the measurement of dissolved oxygen in biotech and pharma applications. It has significant advantages compared to classical Clark cells. It's designed for applications where SIP, CIP, and autoclavations are carried out frequently. Available with the innovative Arc technology.

### BENEFITS

- Robust design for steam sterilization, autoclavation, and CIP
- Self-diagnostics
- Electrolyte-free
- No polarization time required
- Easily replaceable sensor cap
- Digital and analog (4–20 mA) signal output
- ECS-mode available (Clark cell simulation)
- M12 sensor is explosion rated, two-wire, loop-powered 4–20 mA/HART



## OxyFerm FDA

The OxyFerm family of electrochemical (amperometric) oxygen sensors is designed for use in biotechnology applications. Available in different shapes and the innovative Arc technology.

### BENEFITS

- Robust design for steam sterilization, autoclavation, and CIP
- 12 mm or 25 mm shaft (XL) diameter available
- Various O-Ring positions for the XL-version available
- Polarization module available



## Conducell 4UxF

The Conducell 4UxF family of 4-pole conductivity sensors is suitable to measure a broad range of conductivities with excellent linearity. Typical applications are monitoring of CIP cleaning and chromatography. Available with the innovative Arc technology.

### BENEFITS

- Robust design for steam sterilization, auto clavation, and CIP
- All wetted parts are FDA-compliant
- Very easy to clean due to the forward-facing, flush arrangement of electrodes
- EHEDG-certified with Hamilton's hygienic socket
- Available pole materials: stainless steel, Hastelloy C, and titanium
- Various process connections available: PG 13, 5, Tuchenhagen VariVent, BioConnect, and Triclamp




## Conducell UPW

The Conducell UPW (Ultra-Pure Water) 2-pole conductivity sensors are designed for the use in liquids with very low conductivity, i.e. Ultra-Pure Water (UPW), Pure Water (PW), Water For Injection (WFI), particularly in the pharmaceutical industry. Available with the innovative Arc technology.

### BENEFITS

- Monitoring of ultra-pure water according to USP 645 with two alarm outputs
- All wetted parts are FDA-compliant
- Shaft diameters 17 and 12 mm available
- Various process connections available



## Incyte Arc

The Incyte sensors enable real-time, online measurement of viable cells in mammalian cell culture, yeast, and high-density bacterial fermentation. Online measurement allows detection of events and response in real-time without sampling.

### BENEFITS

- Insensitive to media changes, microcarriers, dead cells
- Detect changes in physiology with frequency scanning
- Early detection of deviations without sampling
- Increase yield and lower production costs



## Dencytee Arc

The Dencytee Arc sensors perform online measurement of total cell density based on optical density at NIR (near infrared) wavelengths. Thanks to its combined measuring principle of transmission and reflection measurement, Dencytee Arc delivers reliable TCD values over the complete process at low and high cell concentrations.

### BENEFITS

- Simple on-line measurement of cell growth
- Reliable values during the growth phase
- Improved linearity at high concentrations
- Early detection of process deviations



[www.hamiltoncompany.com/cell-density](http://www.hamiltoncompany.com/cell-density)

## CO<sub>2</sub>

## CO<sub>2</sub>NTROL

The CO<sub>2</sub>NTROL sensor performs online measurement of dissolved carbon dioxide using MIR (mid infrared) wavelengths.

### BENEFITS

- Direct quantification of dissolved CO<sub>2</sub>
- Solid-state sensor requiring minimal maintenance
- Enables real-time CO<sub>2</sub> control for optimizing product yield
- EHEDG certified



# Housings

## Retractex B

Retractex B housings are designed for sanitary applications in biotechnology, food & beverage, and pharmaceutical industry and require low maintenance. The Retractex B with its patented HyCIP cleaning principle offers the best available cleaning efficiency for Ingold sockets.



### BENEFITS

- All major process connections available: Ingold (G1¼), Triclamp, Varivent, DIN 11851
- Pneumatic or manual drive
- Integrated safety concept: no sensor—no insertion
- Very low maintenance



## FlexiFit

FlexiFit static housings are designed for 120 mm sensors.



### BENEFITS

- All major process connections available: Ingold (G1¼), Triclamp, Varivent
- Available with or without protecting rods
- Angled versions available (15°)
- Various O-Ring positions available



## FlowCell

FlowCells are flow-through armatures. They can be used in all cases where pH, DO, conductivity, CO<sub>2</sub>, or even two of them must be reliably measured in chromatography media, as well as in cooling piping in power generation stations.



### BENEFITS

- Flexible design for one or two parameters
- PEEK insert of high chemical resistance
- Low dead volume (less than 8 mL)
- Self draining
- Internal aseptic clamp pipe connection



# Calibration

## pH Buffers

A complete range of buffer solutions provides never before achieved pH stability. Hamilton guarantees that DuraCal pH buffers will be stable for years after the date of manufacturing. Primary and secondary standards are used for the calibration of the devices and the manufacturing of the buffers.

### BENEFITS

- pH 1.09 to pH 12.0 available
- Stability for up to 5 years
- All buffer solutions certified by external laboratory (DAKKS) and traceable to NIST
- Built-in compartment for very convenient calibrations




## Conductivity Standards

Hamilton is the first manufacturer to offer conductivity standards in 1.3 and 5 µS/cm with a certified accuracy of ± 1%. Repeated use is possible if the bottle is not open for more than 1 h in total.

### BENEFITS

- Wide range from 1.3 µS/cm to 100 mS/cm available
- Long time stability up to 3 years at 1% accuracy
- Range from 1.3 µS/cm to 12,880 µS/cm certified by the Danish Institute of Fundamental Metrology and traceable to NIST

# Unlock the Secrets of Bioprocessing Excellence



Part 1



Part 2



©2023 Hamilton Bonaduz A.G. All rights reserved.  
All other trademarks are owned and/or registered by Hamilton Company in the U.S. and/or other countries.

REF 691123/07 — 06/2023

# HAMILTON<sup>®</sup>

Web: [www.hamiltoncompany.com](http://www.hamiltoncompany.com)

USA: 800-648-5950

Europe: +41-58-610-10-10

## Hamilton Americas & Pacific Rim

Hamilton Company Inc.  
4970 Energy Way  
Reno, Nevada 89502 USA  
Tel: +1-775-858-3000  
Fax: +1-775-856-7259  
[sales@hamiltoncompany.com](mailto:sales@hamiltoncompany.com)

## Hamilton Europe, Asia & Africa

Hamilton Bonaduz A.G.  
Via Crusch 8  
CH-7402 Bonaduz, Switzerland  
Tel: +41-58-610-10-10  
[contact.pa.ch@hamilton.ch](mailto:contact.pa.ch@hamilton.ch)

To find a representative in your area, please visit [hamiltoncompany.com/contacts](http://hamiltoncompany.com/contacts).